







# Strong, Pull-Tight Barrier Seal

## ISO 17712 "H" Compliant · C-TPAT Compliant

The Cable Lock 350 is user-friendly, highly tamper-evident, and is available with different cable lengths to secure various applications with different security requirements.

The Cable Lock 350 is secured as soon as the cable has passed through the one-way locking mechanism. The wire must be adjusted to fit tightly to the application to maximize security and prevent tampering.

A strong and versatile seal, it is used widely for securing trucks, tanker trucks, air cargo containers, shipping containers, rail cars, calibrators and valves.

### **Features**

- 1 The exterior of the Cable Lock 350 has been designed with a rib pattern, which protects markings during rough handling.
- 2 The one-way locking mechanism allows for quick and easy application and sealing.
- 3 One end of the cable is permanently secured into the locking body.
- 4 The Cable Lock 350 is anodized in solid colors for a base to print customized laser marking. Anodizing also makes color coding possible and allows for easy identification from a distance.
- 5 The seal is laser engraved with permanent laser marking for company names, logos, sequential numbers and bar codes. Laser marking offers the highest level of security as it cannot be removed or replaced.

## **Technical Specifications**

### **PRODUCT**

**Cable Lock** 

350

**Product** Material Code

> Body: Aluminum body Cable: Galvanized steel wire

Cable Length 356.0 mm

(14.02 inches)

Cable Diameter Ø 3.5 mm

 $(\emptyset \ 0.14 \ in)$ 

Tensile Strength 1200 kgs

(2646 lbs)

Marking

**Marking Digits** 

**Body:** 30.0 x 30.0mm (1.18 x 1.18 in) 15

## **INNER CARTON**

#### **OUTER CARTON**

**Product** Carton Dimensions Weight Code Quantity inches lbs/carton Carton Quantity **Dimensions** inches

Weight lbs/carton

**Cable Lock** 350

200 pcs 17.5 x 10 x 5.5 in 24 lbs

2400 pcs

36 x 32 x 12.2 in

288 lbs

Standard Colors

Carton size/ weight will vary according to customized cable lengths for this seal. Please contact us for additional details.















